NEW AUSSIE SIZZLERCOMPACT | SIMPLE TO USE

BUILT TOUGH



SAVE TIME & CLEAN CHEMICAL FREE, WITH AUSSIE'S NEW COMPACT, HOT WATER BLASTER

- Heavy duty, high efficiency triplex pump with brass head & independent brass unloader
- Adjustable temperature to 80°C
- 4 pole slow speed, air cooled motor with thermal cut-out (10 amp plug fitted)
- Stainless steel cover for protection
- Double loop mild steel coil
- Low maintenance stainless steel boiler, high efficiency with low diesel consumption (3.2 kg/h at full temp)
- Cover lifts off for easy access to internals for maintenance and service.
- Steel chassis with four large wheels for manoeuvrability
- New accessories storage holder
- 18 litre diesel tank (high density polyethylene)

Optional accessories FASTER, SMARTER, SAFER

Turbo Lance 60% MORE BITE

p 59

Increase the effective working pressure (EWP) of your blaster without loading the pump!



CTN255-035

\$198

CLEAN FLAT SURFACES FAST

Clean flat surfaces four times faster, leaving a streak free finish. Standard nozzles included.

SLASH CLEANING TIMES BY 75%

AGPDFSCS22Z **\$1,449** (22" Cyclone, stainless steel)



5,000 psi Stainless Steel Hose Reel

Store extra length hoses, suited for hot water hose up to 5,000 psi, must be wall mounted.

HAR150 (holds up to 45m) \$611 HAR151 (holds up to 75m) \$770 AHW06FB6FB6X2 (2m whip hose) MPA13.5051.51 (3/8" nipple) MPA26065050 (M24 QC)



\$13 \$37

- Multifunction safety control ...
 - Delayed Total Stop ... stops machine 30 seconds after the gun trigger closes ... SAVES FUEL
 - Micro-leak detection ... Stops the machine in case of leaks in hydraulic circuit
 - Nozzle clogged control ... Stops the machine if the nozzle in the end of the lance is blocked
 - Flooding prevention system
 - Intelligent Auto Switch Off ... Switches off machine after 20 minutes of non use.
 - Dry running Protection ... stops the machine when no water is supplied.
 - Ignition boiler delay ... Ensures low fume emissions when boiler starts up.
- Optional stainless steel protective roll frame & lifting bar (as shown in image)

Specifications

Specifications									
	Pressure	EWP with turbo	Flow	Max Temp	Motor	Pump	Nozzle size	Weight	Unit dimensions (Lxwxh) mm
Aussie Sizzler	1,800 psi (130 bar)	3,100 psi	10 lpm	80°C	240v, 2.7kW, 4 pole	Interpump	035	100 kg	820 x 630 x 870

Stock codes & prices

Aussie Sizzler	FS-D1310P4M	\$4,420
SS Protective	AFRAMES/SIZZLER	\$595

Accessories supplied with machine

Hose	AHW06M22X2X8	8m R2 3/8
Gun	M4022209003	AL55 4,500 psi Pro Gun
Lance	C3905.14	700mm single lance
Nozzle	C915035M	Laser Cut (15°)

