JULY 2023





MOBILE CLEANING POWER

Heavy duty self contained systems with integrated water tank ... truly independent cleaning for professional cleaning contractors. Ideal for urban graffiti removal or remote cleaning applications

- Hydrotek self contained steam cleaner .. Diesel or petrol powered with diesel fired burner.
- 880 litre poly impact resistant water tank with position locking lid & water filter (larger tanks available on request)
- 20" Aussie Spinner flat surface cleaner
- Heavy duty stainless steel hose reel with 30 m high pressure hose
- Low pressure hose reel with 30 metres of low pressure supply hose
- Hand gun with stainless steel 700mm dual lance & nozzle kit (except on machines fitted for dual gun operation)
- *Two gun operation available on selected models (reduces flow to 10 lpm per gun)

Tool box options

Trailer Spec ...

Heavy duty Australian made flat bed trailer (Single axle on HSS units & tandem axle on HSC

- Hot dipped galvanised finish
- New wheels & tyres
- Fitted with brakes
- Heavy duty tool box for storage of wash down accessories ... HSC units only.
- Trailer provided with on road NSW blue slip ready for registration.
- **Battery ordered separately** (ABATTERYHW \$240)

Specifications


	Safety Class	Pressure	EWP / turbo	Flow	Max Temp	Burner voltage	Engine	Pump	Nozzle size
PETROL POWERED)								
HSS40005НН	A	4,000 psi (275 bar)	6,485 psi	18 lpm	130°C	12v	Honda GX630	AR	045 (15°, 40°) 035 (25° steam)
HSC40005HAF#	Α	4,000 psi (275 bar)	6,485 psi	20 lpm	130°C	110v	Honda GX630	Bertolini	025,035,045, 050 (all 15°)
DIESEL POWERED	DIESEL POWERED								
HSCX40005DB12	А	4,000 psi (275 bar)	6,485 psi	20 lpm	130°C	12v	Kubota 17HP	Interpump TSF 1819	050 (Q type, 15°,25°,40°)
HSCX40005DG	А	4,000 psi (275 bar)	6,485 psi	20 lpm	130°C	110v	Kubota 17HP	Interpump TSF 1819	050 (Q type, 15°,25°,40°)

Stock codes & pricing

	=					
	Dimensions (LxWxH) m					
HSS40005HH	HSS40005HHJAW	4 x 2 x 1.8	poa			
HSC40005HAF	HSC40005HAFJAW	4 x 2 x 1.8	poa			
HSCX40005DB12	HSCX40005DB12JAW	4 x 2 x 1.8	poa			
HSCX40005DG	HSCX40005DGJAW	4 x 2 x 1.8	poa			




Hose	AHW06M22X2X30	30m R2 3/8"
Gun	CGPDG5010	5,000 psi pro gun
Lance	C3905.16 + CD10073	1200mm single lance



FASTER, SMARTER, SAFER

Optional accessories



Optional hose reel for two gun set -up



Head only (with Quick Coupler tail) CTN400-(insert nozzle size) \$367 CD10077 (coupling to suit)

CLEAN FLAT SURFACES EXTRA FAST p 75

SLASH CLEANING TIMES BY 75% Stainless steel flat surface cleaners

Clean four times faster, leaving a streak free finish. Standard nozzles included

(22"Cyclone 80°C max) HANT28 \$3.109 (28" Twister 120°C max)

AGPDFSC22Z **\$1,624**



Drain Clearing Kit, SAFE & SIMPLE

Includes Aussie Viper Mini Reel with 60 metres of 3/16" sewer hose. Full Aussie Jetters Tool Box, including quick coupler to fit to end of blaster high pressure hose. Includes Safety Plate.

ADRAINKIT Deluxe, stainless steel mini reel version ADRAINKIT-SS \$4.238



see p 48 – 50

MINE SPEC STEAM CLEANERS

SKID MOUNT





A skid or trailer mounted Mine Spec series mobile steam cleaner with it's own water supply. Ideal for on site cleaning!

Aussie Mine Spec Skid/Trailer mount details

- Aussie Hydrotek self contained steam cleaner
- 880 L water tank with float, drain valve, low level cut out sensor, lid with strainer and level indicator (Additional sizes available.)
- Heavy duty skid base or trailer with anti-vibration dampeners and lifting points (cube mounted option available)
- Double stacker unit (supplied separately) with
 - High pressure reel and base mount with 30 metres of 3/8" R2 high pressure outlet hose and screw quick couplings
 - low pressure reel and 30 metres ¾"
 heavy duty reinforced supply hose

- Battery ordered separately (ABATTERYHW)
- # Aussie Mine Spec trailer specs ...

Heavy duty tandem axle trailer

- Hot dipped galvanised finish
- New 15" 6 stud Land Cruiser pattern wheels
- New 31.5 mud pattern tyres
- Extra wide mudguards to suit
- AL-KO Ring coupling with hand brake plate
- Supplied with Brakes
- Heavy Duty tool box for wash down accessories
- Vin numbered , weighed and blue slipped ready for Registration

Optional Extreme Series trailer ... poa

4.5 Tonne GVM Australian made tandem axle flat bed trailer will be provided with the following specifications:-

- Hot dipped galvanised finish
- Rocker roller suspension (4490kg) 63mm square axles (2.4T rated each)
- Four 15" white spoke wheels with off road mud pattern tyres & checker plate mudguards
- Heavy duty landing leg & two stabilizer legs
- Hitch attach options
- Checker plate front and rear mount decks
- Electric brakes standard, other options available

Specifications

	Safety Class	Pressure	EWP with turbo	Flow	Max Temp	Burner voltage	Engine	Pump	Nozzle size
DIESEL POWERED									
HSCX40005D12	А	4,000 psi (275 bar)	6,485 psi	20 lpm	130°C	12v	Kubota 17HP	Interpump TSF 1819	050 (Q type, 15°,25°,40°)
HSC50005D*	В	5,000 psi (350 bar)	8,500 psi	18 lpm	130°C	110v	Kubota 20HP	Interpump TSF 1821	040 (M type, 15°,25°,40°)

Aussie Mine spec includes

- ◆ Emergency stop
- Fire extinguisher (2 Kg)
- ♦ Lockable battery isolator



Stock codes & pricing

	(Hydrotek + 8	Skid mou 80L tank & d	nt version louble stacker hose	Trailer mount version (Hydrotek + 800L tank & double stacker hose reels)			
		Weight	Dim (LxWxH) m			Dim (LxWxH) m	
HSCX40005D12	HSCX40005D12MSM	420 kg	2.03 x 1.3 x 1.2	poa	HSCX40005D12MTR	4 x 2 x 1.8	poa
HSC50005D*	HSC50005DMSM	480 kg	2.03 x 1.3 x 1.2	poa	HSC50005DMTR	4 x 2 x 1.8	poa

Accessories supplied with machine

Hose	AHW06M22X2X30	30m R2 3/8"
Gun	CGPDG5010	5,000 psi pro gun
Lance	C3905.16 + CD10073	1200mm single lance



Class B machines supplied with emergency stop & FREE hose restraint