

HYDRO-TEK MOBI STEAM BLASTERS

The **Hydrotek series** are high pressure, mobile steam cleaners with serious cleaning power. They are self contained so no external power or water source is required.



HSC40005HAF skid mount



A skid mounted mobile steam cleaner with it's own water supply that is ideal for on site cleaning for plant and equipment!

- ♦ **Aussie Hydrotek** self contained steam cleaner
- ♦ **880L water tank** with float, drain valve, low level cut out sensor, lid with strainer and level indicator (Additional sizes available.)
- ♦ **Heavy duty skid base** with anti-vibration dampeners and lifting points (cube mounted option available)
- ♦ **Double stacker hose reel** (supplied separately)
- ♦ **High pressure reel** and base mount with 30 metres of 3/8" R2 high pressure outlet hose and screw quick couplings
- ♦ **Low pressure reel** and 30 metres 3/4" heavy duty reinforced supply hose
- ♦ **Two gun operation** available on selected models
- ♦ **Battery ordered separately** (ABATTERYHW \$240)

Specifications

	Safety Class	Pressure	EWI with turbo	Flow	Max Temp	Burner voltage	Engine	Pump	Nozzle size
PETROL POWERED									
HSS40005HH	A	4,000 psi (275 bar)	6,485 psi	18 lpm	130°C	12v	Honda GX630	AR	045 (15°, 40°) 035 (25° steam)
HSC40005HAF#	A	4,000 psi (275 bar)	6,485 psi	20 lpm	130°C	110v	Honda GX630	Bertolini	025,035,045, 050 (all 15°)
DIESEL POWERED									
HSCX40005DB12	A	4,000 psi (275 bar)	6,485 psi	20 lpm	130°C	12v	Kubota 17HP	Interpump TSF 1819	050 (Q type, 15°,25°,40°)
HSCX40005DG	A	4,000 psi (275 bar)	6,485 psi	20 lpm	130°C	110v	Kubota 17HP	Interpump TSF 1819	050 (Q type, 15°,25°,40°)

Stock codes & pricing

		Weight & Dimensions (LxWxH) m		
HSS40005HH	HSS40005HHSM	1150 kg	2.03 x 1.3 x 1.2	poa
HSC40005HAF#	HSC40005HAFSM	1250 kg	2.03 x 1.3 x 1.2	poa
HSCX40005DB12	HSCX40005DB12SM	1300 kg	2.03 x 1.3 x 1.2	poa
HSCX40005DG	HSCX40005DGSM	1300 kg	2.03 x 1.3 x 1.2	poa

Accessories supplied with machine

Hose	AHW06M22X2X10	10m R2 3/8"
Gun	CGPDG5010	5,000 psi pro gun
Lance	C3905.16 + CD10073	1200mm single lance



see p 48 – 50

Optional accessories FASTER, SMARTER, SAFER

Turbo Kit 60% MORE BITE

p 59

Turbo lance/gun kit.... Increase the effective working pressure of your blaster!



CTN400-__GLK	(insert nozzle size)	\$489
Head only (with Quick Coupler tail)		
CTN400-__H	(insert nozzle size)	\$367
CD10077	(coupling to suit)	\$13

CLEAN FLAT SURFACES FAST

p 75

SLASH CLEANING TIMES BY 75%

Stainless steel flat surface cleaners

Clean four times faster, leaving a streak free finish. Standard nozzles included



AGPDFSC22Z	\$1,624
(22" Cyclone 80°C max)	
HANT28	\$3,109
(28" Twister 120°C max)	

Drain Clearing Kit, SAFE & SIMPLE

p 73

Includes **Aussie Viper Mini Reel** with 60 metres of 3/16" sewer hose. Full Aussie Jetties Tool Box, including quick coupler to fit to end of blaster high pressure hose and safety plate.



ADRAINKIT	\$3,589
Deluxe, stainless steel mini reel version	
ADRAINKIT-SS	\$4,238



MINE SPEC STEAM CLEANERS

SKID MOUNT



This version shows side mounted reels

TRAILER MOUNT



Super heavy duty site trailer

A skid or trailer mounted Mine Spec series mobile steam cleaner with it's own water supply. Ideal for on site cleaning!

Aussie Mine Spec Skid/Trailer mount details

- ◆ Aussie Hydrotek self contained steam cleaner
- ◆ 880 L water tank with float, drain valve, low level cut out sensor, lid with strainer and level indicator (Additional sizes available.)
- ◆ Heavy duty skid base or trailer with anti-vibration dampeners and lifting points (cube mounted option available)
- ◆ Double stacker unit (supplied separately) with
 - ◆ High pressure reel and base mount with 30 metres of 3/8" R2 high pressure outlet hose and screw quick couplings
 - ◆ low pressure reel and 30 metres 3/4" heavy duty reinforced supply hose
- ◆ **Battery ordered separately (ABATTERYHW)**
- ◆ **# Aussie Mine Spec trailer specs ...**
 - Heavy duty tandem axle trailer
 - ◆ Hot dipped galvanised finish
 - ◆ New 15" 6 stud Land Cruiser pattern wheels
 - ◆ New 31.5 mud pattern tyres
 - ◆ Extra wide mudguards to suit
 - ◆ AL-KO Ring coupling with hand brake plate
 - ◆ Supplied with Brakes
 - ◆ Heavy Duty tool box for wash down accessories
 - ◆ Vin numbered , weighed and blue slipped ready for Registration

Optional Extreme Series trailer ... poa

4.5 Tonne GVM Australian made tandem axle flat bed trailer will be provided with the following specifications:-

- ◆ Hot dipped galvanised finish
- ◆ Rocker roller suspension (4490kg) 63mm square axles (2.4T rated each)
- ◆ Four 15" white spoke wheels with off road mud pattern tyres & checker plate mudguards
- ◆ Heavy duty landing leg & two stabilizer legs
- ◆ Hitch attach options
- ◆ Checker plate front and rear mount decks
- ◆ Electric brakes standard, other options available

Specifications

	Safety Class	Pressure	EWP with turbo	Flow	Max Temp	Burner voltage	Engine	Pump	Nozzle size
DIESEL POWERED									
HSCX40005D12	A	4,000 psi (275 bar)	6,485 psi	20 lpm	130°C	12v	Kubota 17HP	Interpump TSF 1819	050 (Q type, 15°,25°,40°)
HSC50005D*	B	5,000 psi (350 bar)	8,500 psi	18 lpm	130°C	110v	Kubota 20HP	Interpump TSF 1821	040 (M type, 15°,25°,40°)

Aussie Mine spec includes

- ◆ Emergency stop
- ◆ Fire extinguisher (2 Kg)
- ◆ Lockable battery isolator



Stock codes & pricing

Skid mount version (Hydrotek + 880L tank & double stacker hose reels)				Trailer mount version (Hydrotek + 800L tank & double stacker hose reels)			
		Weight	Dim (LxWxH) m			Dim (LxWxH) m	
HSCX40005D12	HSCX40005D12MSM	420 kg	2.03 x 1.3 x 1.2	poa	HSCX40005D12MTR	4 x 2 x 1.8	poa
HSC50005D*	HSC50005DMSM	480 kg	2.03 x 1.3 x 1.2	poa	HSC50005DMTR	4 x 2 x 1.8	poa

Accessories supplied with machine

Hose	AHW06M22X2X30	30m R2 3/8"
Gun	CGPDG5010	5,000 psi pro gun
Lance	C3905.16 + CD10073	1200mm single lance



Class B machines supplied with **emergency stop & FREE hose restraint**