



# Aussie Pumps

## HIGH FLOW HYDROSTATIC TESTERS

**NEW**  
STAINLESS  
STEEL FRAME

Leak detection in pipework,  
Oil & gas pipe testing,  
Hydrostatic testing of pumps,  
valves or boilers

# Aussie Pumps

RELIABLE PRODUCTS ... RELIABLE PEOPLE  
[www.aussiepumps.com.au](http://www.aussiepumps.com.au)



## HIGH FLOW HYDROSTATIC TESTERS



This range of hydrostatic testers consist of reliable Udor diaphragm pumps driven by petrol or diesel engines.

- High flow pumps to 125 litres per minute, pressures to 4,000 kPa
  - Reliable Udor pumps standard
  - Simple diaphragm design pump
  - In line strainers standard
  - Double pressure gauge and lock off valve system
  - Integrated control system
  - Gear box drive, enclosed
  - Heavy duty trolley with four big flat free tyres
- Applications:**
- Leak detection in water pipelines
  - Hydrostatic testing of boilers
  - Hydrostatic testing of pressure vessels
  - Oil or gas pipeline testing
  - Hydrostatic testing of pumps, valves or fire mains

# these units are shipped on a skid, dimensions & weight include skid.

\* electric start option available

### HONDA PETROL ... 3 YEAR ENGINE WARRANTY

Model	S/code	Max Pump Pressure (psi)	Max Flow (lpm)	Engine	Pump (rpm)	Boxed Dimensions (LxWxH) mm	Weight (kg)
Kappa 43 HTP*	SKAPPA43/HTP200	580 (40 bar) 4,000 kPa	44	HONDA 6.5HP recoil start	550	1100x800x900	50
Delta 75 HTP*	SDELTA75HTP390	580 (40 bar) 4,000 kPa	73	HONDA 13HP recoil start	550	1100x800x950	110 <sup>#</sup>
Delta 125 HTP*	SDELTA125HTP390	435 (30 bar) 3,000 kPa	125	HONDA 13HP recoil start	550	1100x800x950	120 <sup>#</sup>

### YANMAR DIESEL ... 2 YEAR ENGINE WARRANTY

Note: Pressure and flow figures are expressed as pump maximums. Horsepower limitations may affect pressure/flow combinations.

Model	S/code	Max Pump Pressure (psi)	Max Flow (lpm)	Engine	Pump (rpm)	Boxed Dimensions (LxWxH) mm	Weight (kg)
Kappa 43 D HTP	SKAPPA43HTPL48E	580 (40 bar) 4,000 kPa	44	<b>YANMAR</b> 4.8HP electric start	550	1100x800x950	65 <sup>#</sup>
Delta 75 D HTP	SDELTA75L100HTP	580 (40 bar) 4,000 kPa	75	<b>YANMAR</b> 10HP electric start	550	1100x800x950	160 <sup>#</sup>
Delta 125 D HTP	SDELTA125L100HTP	435 (30 bar) 3,000 kPa	125	<b>YANMAR</b> 10HP electric start	550	1100x800x950	170 <sup>#</sup>

### Aussie Mine Boss option ....

includes following extras

- 38mm super robust gal frame
- Balanced lifting bar
- Emergency stop
- Double insulated wiring
- Lockable battery isolation
- Dry cell battery
- Integrated fire extinguisher



### Wash down kit ...

Turbo 400 gun with 30m of 10mm single wire braid hose



Model	S/code	Max Pump Pressure (psi)	Max Flow (lpm)	Engine	Pump (rpm)	Boxed Dimensions (LxWxH) mm	Weight (kg)
Delta 75 D HTP	SDELT75L100HTM3	580 (40 bar) 4,000 kPa	75	<b>YANMAR</b> 10HP electric start	550	1100x800x950	175 <sup>#</sup>
Delta 125 D HTP	SDELTA125L100HTM	435 (30 bar) 3,000 kPa	125	<b>YANMAR</b> 10HP electric start	550	1100x800x950	185 <sup>#</sup>