

## Model Numbers: 20 Bar Units



### **Features**

- · Positive displacement diaphragm design
- Self prime with auto reprime feature
- · Large capacity oil bath in crankcase
- · Easily adapts to P.T.O drive
- Compatible with most fluids including liquid fertilizers
- Handles fluids to 60 degrees F (15 degrees C)
- Multiple diaphragm design
- Interchanges with other brands

# **Product Description:**

Top quality Udor diaphragm pumps designed for long, trouble free life in ag spray applications. Pumps offer limited self priming from 1 1/2 m and flows from 20 litres per minute to 288 litres per minute. Standard with 6 spline P.T.O shaft.

## **Applications:**

- Broad acre spraying
- Spot spraying
  - Machine wash down Ve
- High pressure water transfer
- Sheep jetting
- Golf and turf
- Sugar cane
- · Vegetable
- Viticulture
- Olives
- Cotton

## Benefits

- Delivers consistent flow right through the pressure range
- Fast and easy to prime
- Cool running, reliable
- Suits almost all tractors
- Super versatile
- · Compatible with high temperature applications
- Smooth running
- Permits easy upgrade

Model	Stock Code	No of diaphr.	Flow (l/m)	Bar	PSI	HP	kW	kg	RPM	control unit
IOTA 20	SIOTA 20 IC	2	20	20	290	0.8	0.6	3	600	fitted
ZETA 85	SZETA 85 IC	3	85	20	290	4.2	3.1	12	550	DL3/20
ZETA 100	SZETA 100 IC	3	98	20	290	4.8	3.5	13	550	DL3/20
ZETA 120	SZETA 120 IC	3	111	20	290	5.7	4.2	18	550	DL3/20
ZETA 140	SZETA 140 IC	3	130	20	290	6.7	4.9	18	550	DL3/20
ZETA 170	SZETA 170 IC	4	163	20	290	8.4	6.1	24	550	DL2/20
ZETA 200	SZETA 200 IC	4	191	20	290	9.8	7.2	26	550	LA2/20
ZETA 230	SZETA 230 IC	6	219	20	290	11.2	8.3	36	550	LA2/20
ZETA 260	SZETA 260 IC	6	247	20	290	12.7	9.3	36	550	LA2/20
ZETA 300	SZETA 300 IC	6	288	20	290	14.8	10.9	38	550	LA2/20

### Shaft Configurations ... options

- PTO, gearbox, pulley or hydraulic drive
- Keyed shaft for gearbox
- Single 1 %" 6 spline male PTO shaft and keyed shaft
- 1 ¾" 6 spline male PTO through shaft/shaft and keyed shaft
  For hydraulic drive only
- Plain shaft on one side, female 6 spline 1 %" PTO adaptor on other side
- 1 3/8" 6 spline male/female PTO shaft, VA shaft
- \* Double 1 % " 6 spline male PTO through shaft

### **Optional Accessories**

- Boominator nozzle kit (P/N: SWOBK1) for boom-less spraying
- Galvanised hose reels with 30 metres of high pressure hose (P/N SWHK1)

Gearbox assemblies also available, call Aussie for more details.



Quality

ISO 9001