


AUSSIE GMP PUMPS

ELECTRIC DRIVE CORROSION RESISTANT... 3 YEAR PUMP WARRANTY



B3ZPM-A/B 18kW

Features

- Heavy duty cast construction
- Big open impeller
- Self primes from 6 metres
- Replaceable suction cover
- Close coupled to a heavy duty TEFC single or three phase electric motor IP rated
- Cast iron foot mounting, steel base plate on models 4kW & over
- Carbon/Alumina seals standard, other seal options available
- Max temperature 70°C

Specifications

Suct/Del	Model	kW	Motor	IP rating	Total Head (m)	Capacity (l/m)	Solids Handled (mm)	Bronze CAT no.	Stainless steel CAT no.
1" x 1"	B1KQ-A	0.37	240v 415v	54	12	130	6	EA9M EA9N	-
2" x 2"	B2KQ-A	1.5	240v 415v	54 (55*)	20	440	16	-	EA7T/EA7G
			240v 415v		19	450	16	-	EA7E
		2.2	240v 415v		16	840	27	EB88	EB92
			240v 415v		15	1650	35	EA7V/(EBGH*) EAT1/(EBFF*) EAT2/(EBFH*)	EASM/(EBHF*)
3" x 3"	B3KQ-A	2.2	240v 415v	54 (55*)	16	840	27	EAL1	-
4" x 4"	B4KQ-A	4	415v	55	15	1650	35	EAL2	-
3" x 3"	B3XR-A	4	415v	55	28	1300	19	EALB	EAD2/EALP
		5.5			28	1400	24	EALC	EAC6/EALR
		7.5			30	1500	24	EALD	-
4" x 4"	B4XR-A	15	415v	55	31	2500	39	EAFG	EAAC

High head options ... for transfer long distances or up a steep gradient

2" x 2"	G2TMK-A	2.2	240v 415v	54	34	400	6	EA9H EA4R	- EB85
			415v		35	850	8	EAHS	-
3" x 3"	G3TMK-A	4	415v	55	40	910	10	-	EALV
		5.5			44	850	13	EAHV	EALZ
		7.5			55	1100	16	EAFR	EACD
		11			65	1200	13	EAFD	-
3" x 3"	B3ZPM-A/B	15	415v	55	70	1200	14	EADV	-
		18			76	1200	19	EARV	-
		22							

(*) ... new line motors being introduced on pumps 2.2kW & under with improved efficiency & IP rating

Due to our program of continuous product development the manufacturer reserves the right to alter specifications without notice.

Heavy duty cast **Ni Al bronze** & cast **316 stainless steel**, self priming, centrifugal electric drive pumps with high pressure and flows available in a range of sizes from 1" through to 4".

These pumps are designed for industrial and agricultural tasks. They are fitted with a

Benefits

- » Long trouble free life
- » Pumps small solids in suspension
- » Ready to pump in minimum amount of time
- » Easy access to check valve for servicing
- » Electric motor convenience with compact design for ease of installation. Motor can be easily removed for maintenance without disconnecting pipework from pump
- » Stable, easy to install
- » Flexibility of handled liquids

heavy duty TEFC single or three phase IP rated electric motor. Pumps are available with standard seals in carbon/Alumina with optional Viton, silicon carbide, tungsten carbide.

DNV approval available for some bronze marine pumps.

Applications:

NiAl bronze

- Deck wash down
- Bilge pump out
- Salvage pump
- Marine air conditioning
- Diesel transfer

Cast 316 Stainless steel

- Aggressive water pumping
- Sewage handling
- Acid & solvent pumping
- Industrial food waste
- Agricultural chemical transfer
- AdBlue transfer



B2KQ-A/X 2.2kW
(with new line motor)



B3XR-A/X 4kW



Quality
ISO 9001
SAI GLOBAL

Aussie Pumps

Reliable Products ... Reliable People

AUSSIE GMP PUMPS

ELECTRIC DRIVE CORROSION RESISTANT... 3 YEAR PUMP WARRANTY

Dimensions:

Model	Length - A (mm)	Height - B (mm)	Width - C (mm)
B1KQ-A	335	295	190
B2KQ-A	410 (455*)	294 (307*)	185 (202*)
B3KQ-A	485 (490*)	295 (295*)	190 (202*)
G2TMK-A	530	320	230



(*) ... new line motors being introduced on pumps 2.2kW & under with improved efficiency & IP rating



B2KQ-A/B 2.2kW

Pumps 4kW & over are mounted on a base plate

Model	Length - A (mm)	Height - B (mm)	Width - I (mm)
B3XR-A 4kW	700	450	360
B3XR-A 5.5kW or 7.5kW	790	470	360
B4KQ-A	700	455	360
B4XR-A	1000	544	470
G3TMK-A 5.5kW or 7.5kW	790	467	360
G3TMK-A 11kW	1000	505	470



Rejuvenation kits...

Contain gaskets, mech seal, counterface & complete check valve to make servicing these pumps a breeze.




B3XR-A/B 5.5kW

Due to our program of continuous product development the manufacturer reserves the right to alter specifications without notice.

AUSSIE GMP PUMPS

ELECTRIC DRIVE CORROSION RESISTANT... 3 YEAR PUMP WARRANTY

Performance Curves: 2900 rpm




Golden Rule

Operate pump at the best efficiency point ... 85% of max pump head



G2TMK-A/B 2.2kW



Curves should be used as a guide only, for detailed performance curves contact Aussie Pumps

Optional Accessories:

- Heavy duty suction hoses 2" and 3"
- Medium pressure lay flat delivery hose, working pressure 100 psi
- Carbon ceramic, silicon carbide, tungsten carbide or Viton seals available